

BODY ELECTRICAL

SERVICE DATA

SS1EJ-02

TURN SIGNAL FLASHER	
Flashes/Minute	60 - 120
SPEEDOMETER (USING A SPEEDOMETER)	
Standard indication (mph)	Allowable range (mph)
20	18 - 24
40	38 - 44
60	58 - 66
80	78 - 88
100	98 - 110
120	118 - 132
TACHOMETER (ON-VEHICLE) DC 13.5 V 25°C (77°F)	
Standard indication (RPM)	Allowable range (RPM)
700	630 - 770
1,000	900 - 1,100
2,000	1,875 - 2,125
3,000	2,850 - 3,150
4,000	3,850 - 4,150
5,000	4,850 - 5,150
FUEL RECEIVER GAUGE	
A - B	85.5 - 105.5 Ω
A - C	126 - 150 Ω
B - C	90 - 110 Ω
FUEL SENDER GAUGE	
Float position F: Approx. 15 mm ((0.59 in.)	Approx. 3 Ω
Float position E: Approx. 200 (7.87 in.)	Approx. 110 Ω
ENGINE COOLANT TEMPERATURE RECEIVER GAUGE	
A - B	71 - 79 Ω
A - C	117 - 141 Ω
B - C	185 - 215 Ω
OIL PRESSURE RECEIVER GAUGE	
Resistance	40 - 48 Ω
CRUISE CONTROL SWITCH	
Switch position OFF	No continuity
Switch position RESUME/ACCEL	Approx. 68 Ω
Switch position SET/COAST	Approx. 198 Ω
Switch position CANCEL	Approx. 418 Ω
CRUISE CONTROL ACTUATOR	
1 - 3	Approx. 2 k Ω
2 - 3	Approx. 0.5 - 1.7 k Ω
Actuator control arm free play	0 mm (0 in.)