

IGNITION

SERVICE DATA

SS1EY-03

Firing order	-	1 - 5 - 3 - 6 - 2 - 4
High-tension cord	Resistance Maximum	25 k Ω per cord
Spark plug	Recommended spark plug Correct electrode gap	ND NGK K16R-U BKR5EYA 0.8 mm (0.031 in.)
Ignition coil	Primary coil resistance Secondary coil resistance	at cold at hot at cold at hot 0.36 - 0.55 Ω 0.45 - 0.65 Ω 9.0 - 15.4 k Ω 11.4 - 18.1 k Ω
Distributor	Air gap Pickup coil resistance	0.2 - 0.4 mm (0.008 - 0.016 in.) at cold (G1 - G $\ominus$) (G2 - G $\ominus$) (NE - G $\ominus$) at hot (G1 - G $\ominus$) (G2 - G $\ominus$) (NE - G $\ominus$) 185 - 275 Ω 185 - 275 Ω 185 - 275 Ω 240 - 325 Ω 240 - 325 Ω 240 - 325 Ω
Crankshaft position sensor	Resistance	at cold (NE $\oplus$ - NE $\ominus$) at hot (NE $\oplus$ - NE $\ominus$) 1,630 - 2,740 Ω 2,065 - 3,225 Ω