

TORQUE SPECIFICATION

Part tightened		N·m	kgf·cm	ft·lbf
Fuel line	for union bolt	29	300	22
	for flare nut	30	310	22
Second seat x Body		39	400	29
Fuel pump bracket assembly x Fuel tank		3.9	40	35 in·lbf
Fuel inlet hose x Fuel filter		29	300	22
Fuel inlet pipe x Fuel filter		29	300	22
Fuel filter x Intake manifold		21	210	15
Fuel pressure regulator x Delivery pipe		25	250	18
Delivery pipe x Intake manifold		21	210	15
Fuel inlet pipe x Delivery pipe	Union bolt	29	300	22
	Bolt	20	200	14
Fuel inlet pipe x Fuel filter		29	300	22
Fuel return pipe x Intake manifold		20	200	14
Air intake chamber x Intake manifold		21	210	15
Intake manifold stay x Air intake chamber		36	360	26
Intake manifold stay x Cylinder block		36	360	26
PS reservoir tank x Air intake chamber		18	185	13
Heater inlet pipe x Air intake chamber		20	200	14
Drain plug x Fuel tank		6.5	65	57 in·lbf
Fuel tank breather tube x Fuel tank		1.5	15	13 in·lbf
Fuel tank filler pipe x Fuel tank		3.5	35	31 in·lbf
Fuel tank band x Body		39	400	29
MAF meter x Bracket		6.9	70	61 in·lbf
MAF meter x Air cleaner cap		6.9	70	61 in·lbf
Throttle body x Air intake chamber		21	210	15
Fuel pump resistor x Body		18	185	13
ECT sensor x Cylinder head		24.5	250	17.5
EGR gas temperature sensor x Air intake chamber		20	200	14
Knock sensor x Cylinder block		44	450	33