

ARB DELUXE BULL BARS & WINCH BARS

Year	Type	Features	Winches	Part No.
2006-07	Winch Bar	Airbag Approved, Recessed Indicators, Recessed Fog Lamps ⁵	9.5xp, HS9500, XD9000, M8000	3421210
2003-05	Winch Bar	Airbag Approved, Recessed Indicators, Recessed Fog Lamps ⁵	9.5xp, HS9500, XD9000, M8000	3421200
1986-95	Winch Bar	Recessed Indicators ² , Tow Points, Black	XD9000, M8000, M6000	3414070 ¹
1984-85	Winch Bar	Recessed Indicators, Tow Points, Black	XD9000, M8000, M6000	3414090

¹ Fitment of bar to 4Runner models may require modifications - contact ARB for details.

² 1986-89 Pickups and 1986-95 4Runners require OE indicators from 1989-94 Pickup - **not supplied**.

³ ARB bars #3921030 & 3421010 measure 72" wide and suit models with wide fender flares.

⁴ ARB bar # 3423020 measures 68" wide and suits models with narrow fender flares.

⁵ Optional on this model - ARB part no. 9249FCK

IPF LIGHTS & LIGHTING ACCESSORIES

Year	Type	Recommended Lighting
ALL	ALL	800XSD, 900XS, 900HID, 960S/R, 868CS, 968CS, J-01

SAFARI SNORKELS

Year	Recommended Snorkel	Part No.
1989-94	3.0L, V6 Snorkel - needs modifications	SS130HF
1984-88	2.0L/2.2L Snorkel - needs modifications	SS65HF

Refer to www.safari4x4.com.au for details.

OLD MAN EMU SUSPENSION PRODUCTS

Year/Model	Location	Description	Type	Lift	Quantity	Part No.
2003-07 Models	Front	Light Load - Stock weight - no Bar or Winch	Spring	1.0"	2	OME884 ¹
			Shock		2	N140S
		Medium Load - with Bar or Winch only (70-180lbs)	Spring	2.0"	2	OME885 ¹
			Shock		2	N140S
		Heavy Load - with Bar and Winch (230lbs+)	Spring	2.5"	2	OME886 ¹
			Shock		2	N140S
	Rear	Medium Load	Spring	2.0"	2	OME895
			Shock		2	N141
		Heavy Load (330lbs to GVW)	Spring	2.0"	2	OME896
					2	N142
		Heavy Constant Load (660lbs to GVW)	Spring	2.0"	2	OME897
					2	N142
	Optional	Front Trim Spacer 5mm				OME95PF5
		Lower Shock mount stone guard (recommended)			2	OME661

¹ Important: OME front coils can only be installed with OME Nitrocharger strut and coil seats.

OLD MAN EMU SUSPENSION PRODUCTS

1996-02 Models	Front	Stock/Light Load (0-110lbs)	Spring	1.25"	2	OME880 ¹
			Shock		2	N91SC
		Heavy Load (110-240lbs)	Spring	1.25"	2	OME881 ¹
			Shock		2	N91S
	Rear	Medium Load	Spring	2.0"	2	OME906
			Shock		2	*N86/N86C
		Heavy Load (330lbs to GVW)	Spring	2.5"	2	OME890
			Shock		2	N86
		Heavy Constant Load (660lbs to GVW)	Spring	3.0"	2	OME891
					2	N86
	Optional	Front Trim Packer 5mm				OME95PF5
		Rear Trim Packer 5mm				OME80PF05
		Rear Trim Packer 10mm				OME80PF10

¹ Important: OME front coils can only be installed with OME Nitrocharger strut and coil seats.

*Firmer shock.

OLD MAN EMU SUSPENSION PRODUCTS

<u>Year/Model</u>	<u>Location</u>	<u>Description</u>	<u>Type</u>	<u>Lift</u>	<u>Quantity</u>	<u>Part No.</u>
IFS / Rear Coil Spring 1990-95	Front	Stock/Light Load	Torsion Bars		1	303003 ¹
			Shock		2	N98
	Rear	Medium Load (0 to GVW)	Spring	1.50"	2	OME900
			Shock		2	N72F
		Heavy Constant (330lbs to GVW)	Spring	1.50"	2	OME901
			Shock		2	N72F
	Installation	Steering Damper			1	OMESD33

¹ Adjust front torsion bar for additional height after installing rear springs. Set ride height to 1/3 upper bump stop clearance and 2/3 lower bump stop clearance.

IFS / Rear Leaf Spring Pre 1990	Front	Stock/Light Load	Torsion Bars		1	303003 ¹
			Shock		2	N98
	Rear	Medium Load (0lbs to GVW)	Spring	2.0"	2	CS009R
			Shock		2	*N85/N94
		Heavy Constant (440lbs to GVW)	Spring	2.25"	2	CS010R
			Shock		2	N85
	Installation	Rear Leaf Spring Bushing Kit			2	OMESB6
		U Bolts			4	OMEU53
		Steering Damper			1	OMESD33
	Optional	Greasable Shackle Kit			1	OMEGS3
		Greasable Pin Kit			1	OMEGP3
		Rear Extra Leaf				D5XL

¹ Adjust front torsion bar for additional height after installing rear springs. Set ride height to 1/3 upper bump stop clearance and 2/3 lower bump stop clearance.

² Install OE caster wedges from OE spring pack onto OME springs. Ensure wedges are fitted as per original position.

³ Compare original spring pack height to OME spring pack to determine whether OMEU53 or OMEU53B U bolts are required.

⁴ Extra leaf can be fitted for heavier constant load carrying ability.

OLD MAN EMU SUSPENSION PRODUCTS

All Leaf Springs 1984-85	Front	Stock/Light Load (0-110lbs)	Spring	2.0"	2	CS008FA/B	
			Shock	2.0"	2	N84	
		Heavy Load (110-240lbs)	Spring	2.0"	2	CS009FA/B ¹	
			Shock	2.0"	2	*N93/N84	
	Rear	Medium Load (0lbs to GVW)	Spring	2.0"	2	CS009R ⁷	
			Shock	2.0"	2	*N85/N94 ⁵	
			Shock	2.0"	2	*N89/N95 ⁵	
		Heavy Constant (550lbs to GVW)	Spring	2.25"	2	CS010R ⁷	
			Shock	2.25"	2	N85 ⁵	
			Shock	2.25"	2	N89 ⁵	
	Installation	Front Spring Bushing Kit				2	OMESB5
		Rear Spring Bushing Kit				2	OMESB6
		Front U Bolts				1	OMEU52 ³
		Rear U Bolts				4	OMEU53
		Rear Anti Inversion Kit (Post '84)				1	FK13 ⁵
		Rear Anti Inversion Kit (Pre '84)				1	FK09 ⁵
		Steering Damper				1	OMESD21
Optional	Front Greasable Shackle Kit				1	OMEGS4	
	Rear Greasable Shackle Kit				1	OMEGS3	
	Greasable Pin Kit				2	OMEGP3	
	Front Fitting Kit				1	FK03/FK10 ⁵	
	Front Extra Leaf					D17XL ⁶	
	Rear Extra Leaf					D5XL ⁶	
	Rear Trim Spacer					TP04 ⁷	

¹ A/A spring fitment may be needed on some vehicles for trimming purposes.

² 1985-89 automatic 4Runner requires modified rear springs. Contact OME for details.

³ Shock selection N89/N95 for medium and N89 for heavy applications applies to vehicles up to 1984 due to a 16mm eye and shorter open and closed lengths. Post 1984 vehicles with 19mm eye use N85/N94 for medium applications and N85 for heavy applications.

⁴ OMEU52 is required when fitting CS009FA/B or CS008FA/B springs because original U bolt will foul drag link on full droop. Refer to OME Fitting Manual.

⁵ Pick up models may require an FK03 (saddle correction plates) if the spring seats are distorted. FK10 must be fitted to all models used continually off road. Refer to OME Fitting Manual.

⁶ Extra Leaf can be fitted for heavier constant load carrying ability.

⁷ A trim spacer may be required to trim vehicle. Only to be used on rear springs. Important: Install leaf springs with military wrap at the fixed end.

ARB AIR LOCKER LOCKING DIFFERENTIALS & ACCESSORIES

Year	Axle	Description	Shaft	Spline	Ratio	Part No.
2003-07	Front	8" dia. RG, IFS, 53mm bearing ID	33 (1.31")	30	3.91 & UP	RD111
2003-07		8" dia. RG, IFS, 53mm bearing ID	33 (1.31")	30	3.73 & DN	RD121
To 2002		8" dia. RG, 10 bolt, live axle	33 (1.31")	30	ALL	RD132
To 2002		7.5 dia. RG 10 bolt, IFS	28 (1.1")	27	ALL	RD90
1984-88	Rear	4 cylinder, 45mm carrier bearing	33 (1.31")	30	ALL	RD132 ¹
1988-07		V6, 4WD, 50mm carrier bearing	33 (1.31")	30	ALL	RD132 ²
1988-07		V6,2WD, 45mm carrier bearing	33 (1.31")	30	ALL	RD132 ^{1,2}

¹ Late model 50.00mm (1.969") ID bearings must be used with this specific application.

² Suits open differential carriers only



FJ CRUISER

TOYOTA

ARB DELUXE BULL BARS & WINCH BARS

Year	Type	Features	Winches	Part No.
2007	Winch Bar	Airbag Approved, Recessed Indicators, Recessed Fog Lamps ¹ , Black	9.5xp, HS9500, XD9000, M8000	3420100

¹ Use ARB part no. 9249FCK fog lamp kit

IPF LIGHTS & LIGHTING ACCESSORIES

Year	Part No.	Recommended Lighting
2007	3420100	800XSD, 900XS, 900HID, 960S/R, 868CS, 968CS, J-01C/B

ARB REAR PROTECTION BARS

Year	Description	Part No.
2007	Standard heavy duty recovery point, hi-lift jack points, powder coated satin black.	5620010

ARB SIDE PROTECTION

Year	Type	Part No.
2007	ARB Deluxe Rock Sliders (Pair) Black powder coat	4420100
	ARB Skid Plates for FJ Cruiser Rock Sliders (optional) Black powder coat	4420110

ARB ROOF RACK

Year	Recommended Roof Racks	Part No.
2007	Roof Rack Cage 87" x 44" - Full Roof Length without Mesh Floor	3800040
	Roof Rack Cage 87" x 44" - Full Roof Length with Mesh Floor	3800040M
	Roof Rack - Touring style to hold roof top tent 87"x49"	3800200
	Fit Kit for 87" Long Rack for FJ Cruiser	3720100
	Roof Rack Cage 52" x 44" - Half Roof Length	3800250
	Fit Kit for 52" x 44" Rack for FJ Cruiser	3720110
	Wind Deflector for FJ Cruiser Roof Rack	3700320
	Hi-lift Jack and Shovel holder for ARB Roof Rack	K6202

SAFARI SNORKELS

Year	Recommended Snorkel	Part No.
2007	Coming soon	N/A

OLD MAN EMU SUSPENSION PRODUCTS

Year/Model	Location	Description	Type	Lift	Quantity	Part No.
2007	Front	Light Load - Stock weight - no Bar or Winch	Spring	2.0"	2	OME884 ¹
			Strut		2	N140S
		Medium Load - with Bar or Winch only (70-180lbs)	Spring	2.5"	2	OME885 ¹
			Strut		2	N140S
		Heavy Load - with Bar and Winch (230lbs+)	Spring	3.0"	2	OME886 ¹
			Strut		2	N140S
	Rear	Medium Load	Spring	2.0"	2	OME895
			Shock		2	N141

¹ Important: OME front coils can only be installed with OME Nitrocharger strut and coil seats.

ARB AIR LOCKER LOCKING DIFFERENTIALS & ACCESSORIES

<u>Year</u>	<u>Axle</u>	<u>Description</u>	<u>Shaft</u>	<u>Spline</u>	<u>Ratio</u>	<u>Part No.</u>
2007	Front	8" dia. RG, IFS, 53mm bearing ID	33 (1.31")	30	3.91 & UP	RD111
2007	Front	8" dia. RG, IFS, 53mm bearing ID	33 (1.31")	30	3.73 & DN	RD121
2007	Rear	8" dia RG, 50mm carrier bearing	33 (1.31")	30	ALL	RD132 ^{1,2}

¹ Suits open differential carriers only

² RD132 superceeds RD23 March 2007



HILUX, PICK UP 4WD

TOYOTA

ARB DELUXE BULL BARS & WINCH BARS

<u>Year</u>	<u>Type</u>	<u>Features</u>	<u>Winches</u>	<u>Part No.</u>
1984-85 US pickups	Winch Bar	Recessed Indicators ² Tow Points, Black	XD9000, M8000	3414090
1986-94 US pickups	Winch Bar	Recessed Indicators ² Tow Points, Black	XD9000, M8000	3414070 ¹
1997-01 Hilux/Tiger	Winch Bar	Airbag Approved, Recessed Indicators, Tow Points, for models with Flares, Black	XD9000, M8000, 9.5XP	3414160
2002-05 Hilux/Tiger	Winch Bar	Airbag Approved, Recessed Indicators, Tow Points, for models without Flares, Black	XD9000, M8000, 9.5XP	3414210
2002-05 Hilux/Tiger	Winch Bar	Airbag Approved, Recessed Indicators, Tow Points, for models with Flares, Black	XD9000, M8000, 9.5XP	3414220
2005-06 Hilux/Vigo	Winch Bar	Airbag Approved, Recessed Indicators, Tow Points, for models with Flares, Black	XD9000, M8000, 9.5XP	3414300
2005-06 Hilux/Vigo	Winch Bar	Recessed Indicators, Tow Points, for models with Flares, Black	XD9000, M8000, 9.5XP	3414310

¹ Fitment of Bar to 1986-88 models require modifications.

² 1986-89 Pickups require OE indicators from 1989-94 pickups - not supplied

IPF LIGHTS & LIGHTING ACCESSORIES

<u>Year</u>	<u>Type</u>	<u>Recommended Lighting</u>
1986-94	3414070	800XSD, 868CS, 968CS, J-01

SAFARI SNORKELS

<u>Year</u>	<u>Recommended Snorkel</u>	<u>Part No.</u>
1989-94	3.0L, V6 Snorkel - needs modifications	SS130HF
1984-88	2.0L/2.2L Snorkel - needs modifications	SS65HF

Refer to www.safari4x4.com.au for details.

OLD MAN EMU SUSPENSION PRODUCTS

<u>Model</u>	<u>Location</u>	<u>Description</u>	<u>Type</u>	<u>Lift</u>	<u>Quantity</u>	<u>Part No.</u>
2005-06 Hilux/Vigo	Front	Light/Medium Load (0-110lbs)	Spring	1.0"	2	OME883
			Shock		2	*N167S/N166S
		Heavy Load (110-220lbs)	Spring	1.0"	2	OME884
			Shock		2	N167S
	Rear	Low Lift Light Load	Spring	0.5"	2	CS043R-15
			Shock		2	N168
		Light Load	Spring	1.75"	2	CS043R
			Shock		2	N168
		Medium Load	Spring	1.75"	2	CS044R
			Shock		2	*N169/N168
		Heavy Constant Load (880lbs to GVW)	Spring	1.75"	2	CS045R
			Shock		2	N169
	Installation	Spring Bushing Kit			2	OMESB98
		U Bolts			4	OMEU53
		Greasable Shackle Kit			1	OMEGS14
		Front Trim Packer (optional)			each	OME95PF5
Pickups with IFS & Rear Leafs 1986- 94	Front	Stock/Light Load (0-90lbs)	Torsion Bar		1	303003 ⁸
			Shock		2	N98
	Rear	Medium Load (0lbs to GVW)	Spring	1.75"	2	CS019R
			Shock		2	*N85/N94
		Heavy Constant (440lbs to GVW)	Spring	2.25"	2	CS020R
			Shock		2	*N85/N94
	Installation	Rear Leaf Spring Bushing Kit			2	OMESB43
		Rear U Bolts			4	OMEU53B
		Steering Damper			1	OMESD33
	Optional	Rear Extra Leaf			2	D6XL ⁶

OLD MAN EMU SUSPENSION PRODUCTS

<u>Model</u>	<u>Location</u>	<u>Description</u>	<u>Type</u>	<u>Lift</u>	<u>Quantity</u>	<u>Part No.</u>
All Leaf Spring Pickups 1984-85	Front	Stock/Light Load (0-110lbs)	Spring	2.0"	2	CS008FA/B ¹
			Shock	2.0"	2	N84
		Heavy Load (110-240lbs)	Spring	2.0"	2	CS009FA/B ¹
			Shock	2.0"	2	*N93/N84
	Rear	Medium Load (0lbs to GVW)	Spring	2.0"	2	CS009R ⁷
			Shock	2.0"	2	*N85/N94 ⁵
		Pre '84	Shock	2.0"	2	*N89/N95 ⁵
			Shock	2.0"	2	*N89/N95 ⁵
		Heavy Constant (550lbs to GVW)	Spring	2.25"	2	CS010R ⁷
			Shock	2.25"	2	N85 ⁵
		Pre '84	Shock	2.25"	2	N89 ⁵
	Installation	Front Spring Bushing Kit			2	OMESB5
		Rear Spring Bushing Kit			2	OMESB6
		Front U Bolts			2	OMEU52 ³
		Rear U Bolts			4	OMEU53
		Rear Anti Inversion Kit (Post '84)			1	FK13 ⁶
		Rear Anti Inversion Kit (Pre '84)			1	FK09 ⁶
		Steering Damper			1	OMESD21
	Optional	Front Greasable Shackle Kit			1	OMEGS4
		Rear Greasable Shackle Kit			1	OMEGS3
		Greasable Pin Kit			2	OMEGP3
		Front Fitting Kit			1	FK03/FK10 ⁵
		Front Extra Leaf			each	D17XL ⁷
		Rear Extra Leaf			each	D5XL ⁷
		Rear Trim Spacer			each	TP04 ⁷

¹ A/A spring fitment may be needed on some vehicles for trimming purposes.

² 1985 -89 automatic 4Runner requires modified rear springs. Contact OME for details.

³ Shock selection N89/N95 for medium and N89 for heavy applications applies to vehicles up to 1984 due to a 16mm eye and shorter open and closed lengths. Post 1984 vehicles with 19mm eye use N85/N94 for medium applications and N85 for heavy applications.

⁴ OMEU52 is required when fitting CS008FA/B or CS008FA/B springs because original U bolt will foul drag link on full droop. Refer to OME Fitting Manual.

⁵ Pick up models may require and FK03 (saddle correction plates) if the spring seats are distorted. FK10 must be fitted to all models used continually off road. Refer to OME Fitting Manual.

⁶ Extra Leaf can be fitted for heavier constant load carrying ability.

⁷ A trim spacer may be required to trim vehicle. Only to be used on rear springs. Important: Install leaf springs with military wrap at the fixed end.

⁸ Adjust front torsion bar for additional height after installing rear springs. Set ride height to 1/3 upper bump stop clearance and 2/3 lower bump stop clearance.

*Firmer Shocks

ARB AIR LOCKER LOCKING DIFFERENTIALS & ACCESSORIES

<u>Year</u>	<u>Axle</u>	<u>Description</u>	<u>Shaft</u>	<u>Spline</u>	<u>Ratio</u>	<u>Part No.</u>
ALL	Front	4WD - 10 Bolt, live axle	33 (1.31")	30	ALL	RD132 ²
		4WD - 7.5 dia. RG 10 bolt, IFS	28 (1.1")	27	ALL	RD90 ¹
	Rear	4 Cyl, 1 ton, 8" dia. RG	33 (1.31")	30	ALL	RD132 ²
		V6, 1 ton, 8" dia. RG	33 (1.31")	30	ALL	RD132 ²

¹ Does not fit some 1986-1995 manual hub models with larger 33mm (1.30") dia. 27 spline axle shafts.

² RD132 superceeds RD23 March 2007



LAND CRUISER 40 SERIES

TOYOTA

ARB DELUXE BULL BARS & WINCH BARS

Year	Type	Features	Winches	Part No.
1969-85	Winch Bar	Tow Points, Hi-lift Jack Point, Black	XD9000, M8274, M8000	3420020

IPF LIGHTS & LIGHTING ACCESSORIES

Year	Model	Recommended Lighting
1969-85	Winch Bar	800XSD, 900XS, 900HID, 930S/R, 960S/R, 868CS, 968CS, J-01

SAFARI SNORKELS

Year	Recommended Snorkel	Part No.
1980-1985	2H, 4.0L, Diesel, Left Side Mount	SS400HF

Refer to www.safari4x4.com.au for details.

OLD MAN EMU SUSPENSION PRODUCTS

40 Series SWB	Front	Gas - Stock/Light Load (0-110lbs)	Spring	1.50"	2	CS001F
			Shock		2	N81
		Gas - Heavy Load (110-240lbs)	Spring	1.25"	2	CS002F
			Shock		2	N41
40 Series SWB		Diesel - Light Load (0-110lbs)	Spring	1.50"	2	CS001F
			Shock		2	N81
		Diesel - Heavy Load (110-240lbs)	Spring	1.25"	2	CS002F
			Shock		2	N41
	Rear	Medium Load (0lbs to GVW)	Spring	2.25"	2	CS001R
			Shock		2	*N89/N95
		Heavy Constant (330lbs to GVW)	Spring	2.50"	2	CS002R
			Shock		2	N89
	Installation	Spring Bushing Kit - Pre 1980			4	OMESB30 ¹
		Spring Bushing Kit - Post 1980			4	OMESB1 ¹
		U Bolts			7	OMEU59A
		U Bolt (Early Pre 1980, 25mm spring eye)			1	OMEU59B
		U Bolt (Late Post 1980, 35mm spring eye)			1	OMEU55
		Rear Anti Inversion Kit			1	FK08 ²
		Steering Damper			1	OMESD23
	Optional	Front Greasable Shackle Kit (Pre '80) 15mm pin			1	OMEGB8
		Front Greasable Shackle Kit (Post '80) 18mm pin			1	OMEGB2
		Rear Greasable Shackle Kit (Pre '80) 15mm pin			1	OMEGB9
		Rear Greasable Shackle Kit (Post '80) 18mm pin			1	OMEGB1
		Greasable Pin Kit (Pre '80) 15mm pin			2	OMEGB8
		Greasable Pin Kit (Post '80) 18mm pin			2	OMEGB1
		Front Extra Leaf				D3XL ³
		Rear Extra Leaf				D4XL ³
		Rear Trim Spacer				TP02

¹ OMESB30 suits 35mm spring eye and hanger bracket with 15mm shackle pin hole. OMESB1 suits 35mm spring eye and hanger bracket with 18mm shackle pin hole.

² **FK08 Anti Inversion Kit is mandatory fitment front and rear if greasable shackles are not fitted.**

³ Extra Leaf can be fitted for heavier constant load carrying ability.

*Firmer shock

OLD MAN EMU SUSPENSION PRODUCTS

Model	Location	Description	Type	Lift	Quantity	Part No.
45 Series	Front	Gas - Stock/Light Load (0-110lbs)	Spring	1.50"	2	CS001F
			Shock		2	N81
		Gas - Heavy Load (110-240lbs)	Spring	1.25"	2	CS002F
			Shock		2	*N41/N81
45 Series	Rear	Diesel - Heavy Load (110-240lbs)	Spring	1.25"	2	CS002F
			Shock		2	N41
		Medium Load (0lbs to GVW)	Spring	2.0"	2	CS003R ¹
			Shock	2.0"	2	N42
		Heavy Constant (880lbs to GVW)	Spring	2.0"	2	CS003R ¹
			Shock	2.0"	2	N42
	Installation	Spring bushing Kit (Pre '80)			4	OMESB30 ²
		Spring Bushing Kit (Post '80)			2	OMESB1 ²
		Spring Bushing Kit (Post '80)			2	OMESB79 ²
		U Bolts			3	OMEU59A
		U Bolts (Early)			5	OMEU59B
		U Bolt (Late)			4	OMEU59B
		U Bolt (Late)			1	OMEU55
		Anti Inversion Kit			1	FK08 ³
		Steering Damper			1	OMESD23
	Optional	Front Greasable Shackle Kit (Pre '80)			1	OMEGB8
		Front Greasable Shackle Kit (Post '80)			1	OMEGB2
		Rear Greasable Shackle Kit (Pre '80)			1	OMEGB9
		Rear Greasable Shackle Kit (Post '80)			1	OMEGB1
		Greasable Pin Kit (Pre '80)			2	OMEGP8
		Greasable Pin Kit (Post '80)			2	OMEGP1
		Front Extra Leaf				D3XL ⁴
		Rear Extra Leaf				201XL ⁴
		Rear Trim Spacer				TP02

¹ Remove 3rd leaf from CS003R spring stack to reduce spring rate for medium duty application.

² OMESB30 suits 35mm spring eye and hanger bracket with 15mm shackle pin hole. OMESB1 suits 35mm spring eye and hanger bracket with 18mm shackle pin hole. OMESB79 suits 35mm spring eye with 30mm hanger bracket with 18mm shackle pin hole.

³ FK08 Anti Inversion Kit is mandatory fitment front and rear if greasable shackles are not fitted.

⁴ Extra Leaf can be fitted for heavier constant load carrying ability. Important: Install leaf springs with military wrap at the fixed end.

ARB AIR LOCKER LOCKING DIFFERENTIALS & ACCESSORIES

Year	Axle	Description	Shaft	Spline	Ratio	Part No.
To 1989	Front	12 bolt, full floating	33 (1.31")	30	ALL	RD33 ²
1990-97		10 bolt, full floating	33 (1.31")	30	ALL	RD132 ⁴
1969-76 ¹	Rear	12 bolt, semi floating	33 (1.31")	30	ALL	RD124
1977-89		12 bolt, full floating 45mm bearing ID	33 (1.31")	30	ALL	RD33 ²
1990-97		12 bolt, full floating 50mm bearing ID	33 (1.31")	30	ALL	RD33
1977-92		12 bolt, semi floating	33 (1.31")	30	ALL	RD124
FJ40s ³		Dana 60	30 (1.31")	30	4.56 & UP	RD21
			30 (1.31")	30	4.10 & DN	RD22

¹ Only vehicles made in North America.

² Must use late model 50.00mm (1.969") ID bearings with this application.

³ Only FJ40s made in South America.

⁴ RD132 superceeds RD23 March 2007



LAND CRUISER 60 SERIES

TOYOTA

ARB DELUXE BULL BARS & WINCH BARS

<u>Year</u>	<u>Type</u>	<u>Features</u>	<u>Winches</u>	<u>Part No.</u>
1980-89	Winch Bar	Recessed Indicators, Tow Points, Black	XD9000, M8274, M8000	3410100

IPF LIGHTS & LIGHTING ACCESSORIES

<u>Year</u>	<u>Part No.</u>	<u>Recommended Lighting</u>
1980-89	3410100	800XSD, 900XS, 900HID, 930S/R, 960S/R, 868CS, 968CS, J-01

ARB SIDE RAILS & STEPS

<u>Year</u>	<u>Model</u>	<u>Description</u>	<u>Part No.</u>
1980-89	ALL	Side protection rails and steps (new design to match 3410100). Black	4410020

SAFARI SNORKELS

<u>Year</u>	<u>Recommended Snorkel</u>	<u>Part No.</u>
1980-89	ALL 60 series models	SS60HF

Refer to www.safari4x4.com.au for details.

OLD MAN EMU SUSPENSION PRODUCTS

<u>Model</u>	<u>Location</u>	<u>Description</u>	<u>Type</u>	<u>Lift</u>	<u>Quantity</u>	<u>Part No.</u>
60/61/62	Front	Gas - Stock/Light Load (0-110lbs)	Spring	2.0"	2	CS003F
			Shock		2	*N88/N92
		Gas - Heavy Load (110-240lbs)	Spring	2.0"	2	CS004F ¹
			Shock		2	N88
		Diesel - Stock/Light Load (0-110lbs)	Spring	2.0"	2	CS004F ¹
			Shock		2	*N50/N88
		Diesel - Heavy Load (110-240lbs)	Spring	2.0"	2	CS005F
			Shock		2	N50
	Rear	Stock/Light Load	Spring	3.0"	2	CS017RA/B ²
		Stock/Light Load - Post 1986	Shock		2	N94 ³
		Stock/Light Load - Pre 1986	Shock		2	N95 ³
		Medium Load (0lbs - GVW)	Spring	3.0"	2	CS004RA/B
		Medium Load - Post 1986	Shock		2	*N90/N85 ³
		Medium Load - Pre 1986	Shock		2	*N42/N89 ³
		Heavy Constant (440lbs to GVW)	Spring	3.0"	2	CS005RA/B ²
		Heavy Constant - Post 1986	Shock		2	*N90/N85 ³
		Heavy Constant - Pre 1986	Shock		2	*N42/N89 ³
	Installation	Spring Bushing Kit			4	OMESB1
		Front U Bolts			4	OMEU51 ⁴
		Rear U Bolts			4	OMEU59B ⁴
		Front Fitting Kit			1	FK01 ⁵
		Rear Fitting Kit				See Note ⁵
		Rear Anti Inversion Kit			1	FK08 ⁶
		Steering Damper			1	OMESD24

* Firmer shocks.

OLD MAN EMU SUSPENSION PRODUCTS

<u>Model</u>	<u>Location</u>	<u>Description</u>	<u>Type</u>	<u>Lift</u>	<u>Quantity</u>	<u>Part No.</u>
60/61/62	Optional	Front Greasable Shackle Kit			1	OMEGS2
		Rear Greasable Shackle Kit			1	OMEGS1
		Greasable Pin Kit			2	OMEGP1
		Front Extra Leaf				D1XL ⁷
		Rear Extra Leaf				D2XL ⁷
		Front Trim Spacer				TP01

¹ When bump stop heights exceed 110mm the 4th leaf in the CS004F spring can be removed or CS003F can be used for ride quality and to reinstate desired bump stop height. OMECW2 spring caster wedge may be required to restore positive caster angle.

² Barn door models may require A/A or B/B spring fitment.

³ Post 1986 vehicles have 19mm mounting pin and accept shock part no's N94, N90, & N85. Pre '86 models have 16mm mounting pin and use N95, N42, and N89.

⁴ Compare original spring pack to OME spring pack to determine U bolt.

⁵ Front: FK01 not required if OE U bolts are replaced with OMEU51. Rear: Only required on vehicles with rubber insulators around rear springs. Refer to OME Fitting Manual Section 7 GFI Land Cruiser 60 Series page 7 selection chart.

⁶ **FK08 Anti Inversion Kit is mandatory fitment if greasable shackles are not fitted.**

⁷ Extra Leaf can be fitted for heavier constant load carrying ability. **Important:** Install leaf springs with military wrap at the fixed end.

⁸ CS005F is a modular spring using CS004F spring & 3A/BXL leaf.

ARB AIR LOCKER LOCKING DIFFERENTIALS & ACCESSORIES

<u>Year</u>	<u>Axle</u>	<u>Description</u>	<u>Shaft</u>	<u>Spline</u>	<u>Ratio</u>	<u>Part No.</u>
1980-89	Front	12 bolt, full floating	33 (1.31")	30	ALL	RD33 ¹
	Rear	12 bolt, semi floating	33 (1.31")	30	ALL	RD124
		12 bolt, semi floating (50mm)	33 (1.31")	30	ALL	RD33 ¹
		12 bolt, full floating (45mm)	33 (1.31")	30	ALL	RD33 ¹

¹ Must use late model 50.00 mm (1.969") ID bearings with this application.

ARB ROOF RACKS

<u>Models</u>	<u>Recommended Roof Racks</u>	<u>Part No.</u>
60 Series	87x49" With Mesh Floor	3800010M
	87x49" Without Mesh Floor	3800010
	87x49" Touring Rack for Roof Top Tent	3800200
	87x49" Fitting Kit	3700050
	73x49" With Mesh Floor	3800020M
	73x49" Without Mesh Floor	3800020
	73x49" Fitting Kit	3700050
	43x49" With Mesh Floor	3800030M
	43x49" Fitting Kit	3700060
	Wind Deflector for 49" wide Roof Rack	3700310
	Hi-lift Jack and Shovel holder for ARB Roof Rack	K6202



TOYOTA

LAND CRUISER 70, 73, 74 SERIES

ARB DELUXE BULL BARS & WINCH BARS

<u>Year</u>	<u>Type</u>	<u>Features</u>	<u>Winches</u>	<u>Part No.</u>
All	Winch Bar	Tow Points, Recessed Indicators, Black	9.5XP, M12000, XD9000, M8274, M8000.	3412130

IPF LIGHTS & LIGHTING ACCESSORIES

<u>Year</u>	<u>Model</u>	<u>Recommended Lighting</u>
All	70 Series	800XSD, 900XS, 900HID, 930S/R, 960S/R, 868CS, 968CS, J-01

SAFARI SNORKELS

<u>Year</u>	<u>Recommended Snorkel</u>	<u>Part No.</u>
All	3B Diesel, Right Side Mount.	SS73HF

OLD MAN EMU SUSPENSION PRODUCTS

<u>Model</u>	<u>Location</u>	<u>Description</u>	<u>Type</u>	<u>Lift</u>	<u>Quantity</u>	<u>Part No.</u>
All Gas & Diesel, SWB & MWB 70 Series models	Front	All models - Light Load to 110lbs	Spring	2.0"	2	CS006FM
			Shock		2	*N88/N92
	Installation	Spring Bushing			2	OMESB1
		Greasable Shackle			1	OMEGS2
					1	OMEGP1
		Trim Packer				TP01
		Steering Damper			1	OMESD24
	Front	Heavy Load 110 to 240lbs	Spring	2.0"	2	CS006F
			Shock		2	N88
	Installation	Spring Bushing			2	OMESB1
All Gas & Diesel, SWB & MWB 70 Series models		U Bolt			4	OMEU51
		Greasable Shackle			1	OMEGS2
					1	OMEGP1
		Trim Packer				TP01
		Steering Damper			1	OMESD24
	Rear	Medium Load to GVW	Spring	2.75"	2	CS017RA/B
			Shock		2	N85
	Installation	Spring Bushing			2	OMESB1
		U Bolt			4	OMEU59A
		Greasable Shackle			1	OMEGS2
All Gas & Diesel, SWB & MWB 70 Series models					1	GSP01
	Rear	Constant 440lb Load to GVW	Spring	2.75"	2	CS004RA/B ²
			Shock		2	N85
	Installation	Spring Bushing			2	OMESB1
		U Bolt			4	OMEU59A
		Greasable Shackle			1	OMEGS2
					1	GSP01
		Anti Inversion Kit**			1	FK08

¹ CS006FM is a modified CS006F spring (4th leaf from top of spring stack removed.) Use where bump stop heights exceed 3.93".

² If bump stop measurement exceeds 59-63" remove third leaf from top of spring stack to prevent shock absorber from topping out.

** Anti Inversion Kit FK08 is required for installation if Greasable shackles are not installed.

ARB AIR LOCKER LOCKING DIFFERENTIALS & ACCESSORIES

<u>Year</u>	<u>Axle</u>	<u>Description</u>	<u>Shaft</u>	<u>Spline</u>	<u>Ratio</u>	<u>Part No.</u>
To 1989	Front	12 Bolt	33 (1.31")	30	ALL	RD33
	Rear	12 Bolt, Semi Float	33 (1.31")	30	ALL	RD124