

TORQUE SPECIFICATION

Part tightened	N·m	kgf·cm	ft·lbf
Fuel line			
Union bolt type	39	400	29
Flare nut type	34	345	25
for use with SST	38	380	28
Fuel pressure pulsation damper x Delivery pipe	33	340	24
for use with SST	39	400	29
Fuel pressure regulator x RH delivery pipe	7.5	80	66 in.·lbf
Fuel tank vent tube set plate x Fuel tank	3.5	35	31 in.·lbf
Front fuel pipe x Delivery pipe	39	400	29
Front fuel pipe x Lower intake manifold	7.5	80	66 in.·lbf
Fuel return pipe x LH delivery pipe	7.5	80	66 in.·lbf
Delivery pipe x Lower intake manifold	18	185	13
Fuel sender gauge x Fuel tank	1.5	15	13 in.·lbf
Fuel tank x Body	39	400	29
Drain plug x Fuel tank	6.5	65	58 in.·lbf
Fuel tank filler pipe x Fuel tank	3.5	35	31 in.·lbf
Cutoff valve cover x Fuel tank	1.5	15	13 in.·lbf
Throttle position sensor x Throttle body	2.0	20	18 in.·lbf
Water bypass pipe x Throttle body	5.4	55	48 in.·lbf
Throttle control motor x Throttle body	3.4	35	30 in.·lbf
Throttle control motor cover x Throttle body	3.4	35	30 in.·lbf
Accelerator pedal position sensor x Throttle body	5.4	55	48 in.·lbf
Throttle body x Upper intake manifold, Lower intake manifold	18	185	13
Upper intake manifold, Accelerator cable bracket x Lower intake manifold	18	185	13
ECT sensor x Front water bypass joint	19.6	200	14
Knock sensor x Cylinder block	45	450	33
Heated oxygen sensor x Exhaust manifold	44	450	32
Heated oxygen sensor x Front exhaust pipe	20	200	14