

# BODY

## TORQUE SPECIFICATION

SS00L-02

Part tightened		N·m	kgf·cm	ft·lbf
<b>FRONT BUMPER</b>				
Front bumper cover x Body	Bolt:	8.3	85	74 in.·lbf
Front bumper cover x Body	Screw:	2.9	30	26 in.·lbf
Fog light x Front bumper cover		4.9	50	43 in.·lbf
Front bumper reinforcement x Body		58	590	43
<b>REAR BUMPER</b>				
Rear bumper cover x Body		20	200	14
Reflex reflector x Rear bumper cover		4.9	50	43 in.·lbf
Rear bumper reinforcement x Extension mounting bracket		13	130	9
Extension mounting bracket x Body		19	195	14
<b>HOOD</b>				
Hood support x Body		17	170	12
Hood support x Hood		17	170	12
Radiator grille x Hood		4.9	50	43 in.·lbf
Lower radiator grille bracket x Radiator grille		4.9	50	43 in.·lbf
Lower radiator grille bracket x Body		4.9	50	43 in.·lbf
Hood x Hood hinge		18	185	13
<b>HOOD LOCK CONTROL</b>				
Hood lock x Body	Bolt:	8.0	82	71 in.·lbf
Hood lock x Body	Nut:	8.0	82	71 in.·lbf
<b>FRONT DOOR</b>				
Door glass x Window regulator		5.0	51	44 in.·lbf
Window regulator x Door panel		5.0	51	44 in.·lbf
Door lock x Door panel		5.0	51	44 in.·lbf
Outside handle x Door panel		5.0	51	44 in.·lbf
Door lock cylinder x Outside handle		5.0	51	44 in.·lbf
Door hinge x Body		26	265	19
Door hinge x Door panel		26	265	19
Door lock striker x Body		11	115	8
<b>REAR DOOR</b>				
Door glass x Window regulator		5.0	51	44 in.·lbf
Window regulator x Door panel		5.0	51	44 in.·lbf
Door lock x Door panel		5.0	51	44 in.·lbf
Outside handle x Door panel		5.0	51	44 in.·lbf
Door hinge x Body		26	265	19
Door hinge x Door panel		26	265	19
Door lock striker x Body		11	115	8
<b>UPPER BACK DOOR</b>				
Back door control x Door panel		7.4	75	65 in.·lbf
Outside handle x Door panel		7.4	75	65 in.·lbf
Back door hinge x Body		12	122	9
Back door hinge x Door panel		12	122	9

## SERVICE SPECIFICATIONS – BODY

Door lock striker x Door panel	11	115	8
LOWER BACK DOOR	–	–	–
Back door lock x Door panel	7.4	75	65 in.·lbf
Tail gate stay x Door panel	17	170	12
Tail gate stay x Body	17	170	12
Door hinge x Body	18	184	13
Door hinge x Door panel	18	184	13
Door lock striker x Body	11	115	8
BACK DOOR STAY	–	–	–
Back door stay x Body	17	170	12
Back door stay x Door panel	7.4	75	65 in.·lbf
FRONT WIPER AND WASHER	–	–	–
Wiper arm x Wiper link	20	205	15
Wiper link x Body	5.4	55	48 in.·lbf
REAR WIPER AND WASHER	–	–	–
Wiper motor and link assembly x Door panel	5.4	55	48 in.·lbf
Wiper arm x Wiper link	5.4	55	48 in.·lbf
INSTRUMENT PANEL	–	–	–
Front passenger airbag assembly x Reinforcement	20	204	15
Steering wheel set nut	34	350	25
Front passenger airbag assembly x Instrument panel	6.0	61	53 in.·lbf
SIDE STEP	–	–	–
No.1 side step bracket x Side step	4.9	50	43 in.·lbf
No.1 side step bracket x Body	18	185	13
No.2 side step bracket x Side step	4.9	50	43 in.·lbf
No.2 side step bracket x Body Bolt:	18	185	13
No.2 side step bracket x Body Nut:	12	120	9
No.3 side step bracket x Side step	4.9	50	43 in.·lbf
No.3 side step bracket x Body	18	185	13
FRONT SEAT	–	–	–
Front seat adjuster x Body	42	429	31
Seatback assembly x Seat adjuster	43	440	32
Armrest x Seatback assembly	37	375	27
Seat cushion assembly x Seat adjuster	21	210	15
REAR NO.1 SEAT (LH)	–	–	–
Seat cushion hinge x Body	41	420	30
Seatback assembly x Seat adjuster	41	420	30
Seat adjuster x Seat cushion frame	41	420	30
REAR NO.1 SEAT (RH)	–	–	–
Seat cushion hinge x Body	41	420	30
Seatback assembly x Seat adjuster	41	420	30
Seat adjuster x Seat cushion frame	41	420	30
REAR NO.2 SEAT	–	–	–
Seatback assembly x Reclining adjuster	41	420	30
Reclining adjuster x Seat cushion frame	41	420	30
Seat leg adjuster x Seat cushion frame A Bolt:	18	185	13

Seat leg adjuster x Seat cushion frame	B Bolt:	37	380	27
SEAT BELT		–	–	–
Outer belt shoulder anchor x Adjustable anchor		43	440	32
Outer belt shoulder anchor x Body		43	440	32
Seat belt floor anchor x Body		43	440	32
Retractor x Body	Upper Side:	4.9	50	43 in.:lbf
Retractor x Body	Lower Side:	43	440	32
Retractor x Seatback frame		43	440	32
Inner belt x seat cushion frame		43	440	32
Lap type center with inner belt x Seat cushion frame		43	440	32
Rear seat shoulder belt guide x Seatback frame		43	440	32